


1.1 CONEXIÓN POR TORNILLOS SpeedPro
SCREW CONNECTION SpeedPro

BASES FIJAS PARED ACODADAS 90° / WALL MOUNTED SOCKET 90°

SpeedPRO IP44

base de pared acodada 90° / wall mounted socket 90°



| Poles | 16A | | | 32A | | |
|---------------------|---|-----|-----|---------|-----|-----|
| | 3 | 4 | 5 | 3 | 4 | 5 |
| A | 66 | 66 | 66 | 90 | 90 | 90 |
| B | 86 | 86 | 100 | 100 | 100 | 100 |
| C | 52 | 52 | 77 | 77 | 77 | 77 |
| D | 61 | 61 | 85 | 85 | 85 | 85 |
| E | 95 | 120 | 96 | 140 | 96 | 143 |
| F | 126 | 126 | 136 | 160 | 160 | 160 |
| G | 86 | 94 | 102 | 108 | 108 | 113 |
| Connection type | Conexión por tornillo / Screw terminals | | | | | |
| Wire flexible (mm²) | 1 - 2,5 | | | 2,5 - 6 | | |
| Weight (g) | 172 | 182 | 241 | 290 | 296 | 332 |

- Terminales con tornillo
 - Material: PA6/ABS
 - Contactos: Niquelados
- IP44** a prueba de salpicaduras
- With screw terminals
 - Housing material: PA6/ABS
 - Contacts: Nickel-plated contacts
- IP44** Splashproof

| Amp | Poles | Pack unit | 110V | 230V | 400V | 500V |
|-----|-------|-----------|-------------------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | | | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| | | | Poles: 3P 4P 5P Hour P: 4h 4h 4h | Poles: 3P 4P 5P Hour P: 6h 9h 9h | Poles: 3P 4P 5P Hour P: 9h 6h 6h | Poles: 3P 4P 5P Hour P: 7h 7h 7h |

| Amp | Poles | Pack unit | 110V | 230V | 400V | 500V |
|-----|-------|-----------|---------|---------|---------|---------|
| | | | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| 16 | 3 | 4 | 23150 | 23250 | 23354 | 23454 |
| | 4 | 4 | 23151 | 23251 | 23350 | 23450 |
| | 5 | 2 | 23154 | 23252 | 23351 | 23451 |
| 32 | 3 | 2 | 23152 | 23253 | 23355 | 23455 |
| | 4 | 2 | 23153 | 23254 | 23352 | 23452 |
| | 5 | 2 | 23155 | 23255 | 23353 | 23453 |




Ref. / Item 23250



SpeedPRO IP67

base de pared acodada 90° / wall mounted socket 90°



| Poles | 16A | | | 32A | | |
|---------------------|---|-----|-----|---------|-----|------|
| | 3 | 4 | 5 | 3 | 4 | 5 |
| A | 66 | 66 | 90 | 90 | 90 | 90 |
| B | 86 | 86 | 100 | 100 | 100 | 100 |
| C | 52 | 52 | 77 | 77 | 77 | 77 |
| D | 61 | 61 | 85 | 85 | 85 | 85 |
| E | 95 | 120 | 96 | 140 | 96 | 143 |
| F | 126 | 126 | 136 | 160 | 160 | 160 |
| G | 70 | 78 | 85 | 92 | 92 | 99,5 |
| Connection type | Conexión por tornillo / Screw terminals | | | | | |
| Wire flexible (mm²) | 1 - 2,5 | | | 2,5 - 6 | | |
| Weight (g) | 135 | 215 | 241 | 290 | 296 | 332 |

- Terminales con tornillo
 - Material: PA6/ABS
 - Contactos: Niquelados
- IP67** Hermético
- With screw terminals
 - Housing material: PA6/ABS
 - Contacts: Nickel-plated contacts
- IP67** Watertight

| Amp | Poles | Pack unit | 110V | 230V | 400V | 500V |
|-----|-------|-----------|---------|---------|---------|---------|
| | | | 50/60Hz | 50/60Hz | 50/60Hz | 50/60Hz |
| 16 | 3 | 4 | 24150 | 24250 | 24354 | 24454 |
| | 4 | 4 | 24151 | 24251 | 24350 | 24450 |
| | 5 | 2 | 24154 | 24252 | 24351 | 24451 |
| 32 | 3 | 2 | 24152 | 24253 | 24355 | 24455 |
| | 4 | 2 | 24153 | 24254 | 24352 | 24452 |
| | 5 | 2 | 24155 | 24255 | 24353 | 24453 |



Ref. / Item 24353

